



### D-sluiting met borstbout


Handelskwaliteit  
Niet voor hijstoepassingen geschikt!

Art. nr.	a / mm	b / mm	c / mm	d / mm	e / mm	Prijs (ex btw)
16002005	5	5	10	10	20	
16002006	6	6	12	12	24	
16002008	8	8	16	16	32	
16002010	10	10	20	20	40	
16002013	12	12	24	24	48	
16002016	16	16	32	32	64	
16002019	19	19	38	38	76	
16002022	22	22	44	44	88	
16002025	25	25	50	50	100	



### Harp-sluiting met borstbout

Handelskwaliteit  
Niet voor hijstoepassingen geschikt!



Art. nr.	a / mm	b / mm	c / mm	d / mm	e / mm	f / mm	Prijs (ex btw)
16006005	5	5	10	10	20	15	
16006006	6	6	12	12	24	18	
16006008	8	8	16	16	32	24	
16006010	10	10	20	20	40	30	
16006013	12	12	24	24	48	36	
16006016	16	16	32	32	64	48	
16006019	19	19	38	38	76	57	
16006022	22	22	44	44	88	66	
16006025	25	25	50	50	100	75	
16006038	38	38	76	76	152	114	



### Green Pin® D-sluiting met moerbout G-4153

Materiaal: boog en pen van hoogwaardig staal, Grade 6

Veiligheidsfactor: 6:1

Klasse: EN 13889

Art. nr.	WLL / t	a / mm	b / mm	c / mm	d / mm	e / mm	Prijs (ex btw)
16100016	2	13,5	16	34	43	22	
16100019	3,25	16	19	40	51	27	
16100022	4,75	19	22	46	59	31	
16100025	6,5	22	25	52	73	36	
16100028	8,5	25	28	59	85	43	
16100032	9,5	25	32	66	90	47	
16100035	12	32	35	72	94	51	
16100038	13,5	35	38	80	115	57	
16100042	17	38	42	88	127	60	
16100050	25	45	50	103	149	74	
16100057	35	50	57	111	171	83	
16100065	42,5	57	65	130	190	95	
16100070	55	65	70	145	203	105	
16100080	85	75	83	162	229	127	

### Green Pin® D-sluiting met borstbout G-4151

Materiaal: boog en pen van hoogwaardig staal, Grade 6

Veiligheidsfactor: 6:1

Klasse: EN 13889

Art. nr.	WLL / t	a / mm	b / mm	c / mm	d / mm	e / mm	Prijs (ex btw)
16101006	0,33	5	6	12	19	9,5	
16101008	0,5	7	8	16,5	22	12	
16101010	0,75	9	10	20	26	13,5	
16101011	1	10	11	22,5	32	17	
16101013	1,5	11	13	26,5	37	19	
16101016	2	13,5	16	34	43	22	
16101019	3,25	16	19	40	51	27	
16101022	4,75	19	22	46	59	31	
16101025	6,5	22	25	52	73	36	
16101028	8,5	25	28	59	85	43	



### Green Pin® D-sluiting met borstbout G-4151

Materiaal: boog en pen van hoogwaardig staal, Grade 6

Veiligheidsfactor: 6:1

Klasse: EN 13889

Art. nr.	WLL / t	a / mm	b / mm	c / mm	d / mm	e / mm	Prijs (ex btw)
16101032	9,5	28	32	66	90	47	
16101035	12	32	35	72	94	51	
16101038	13,5	35	38	80	115	57	
16101042	17	38	42	88	127	60	
16101050	25	45	50	103	149	74	
16101057	35	50	57	111	171	83	
16101070	55	65	70	145	203	105	

### Green Pin® Harpsluiting met moetbout G-4163

Materiaal: boog en pen van hoogwaardig staal, Grade 6

Veiligheidsfactor: 6:1

Klasse: EN 13889

Art. nr.	WLL / t	a / mm	b / mm	c / mm	d / mm	e / mm	Prijs (ex btw)
16105008	0,5	7	8	16,5	29	12	
16105010	0,75	9	10	20	32	13,5	
16105011	1	10	11	22,5	36,5	17	
16105013	1,5	11	13	26,5	43	19	
16105016	2	13,5	16	34	51	22	
16105019	3,25	16	19	40	64	27	
16105022	4,75	19	22	46	76	31	
16105025	6,5	22	25	52	83	36	
16105028	8,5	25	28	59	95	43	
16105032	9,5	28	32	66	108	47	
16105035	12	32	35	72	115	51	
16105038	13,5	35	38	80	133	57	
16105042	17	38	42	88	146	60	
16105050	25	45	50	103	178	74	
16105057	35	50	57	111	197	83	
16105065	42,5	57	65	130	222	95	
16105070	55	65	70	145	260	105	



### Green Pin® Harpsluiting met moetbout G-4163

Materiaal: boog en pen van hoogwaardig staal, Grade 6

Veiligheidsfactor: 6:1

Klasse: EN 13889

Art. nr.	WLL / t	a / mm	b / mm	c / mm	d / mm	e / mm	Prijs (ex btw)
16105080	85	75	83	162	329	127	



### Green Pin® Harpsluiting met borstbout G-4161

Materiaal: boog en pen van hoogwaardig staal, Grade 6

Veiligheidsfactor: 6:1

Klasse: EN 13889

Art. nr.	WLL / t	a / mm	b / mm	c / mm	d / mm	e / mm	Prijs (ex btw)
16106006	0,33	5	6	12	22	9,5	
16106008	0,5	7	8	16,5	29	12	
16106010	0,75	9	10	20	32	13,5	
16106011	1	10	11	22,5	36,5	17	
16106013	1,5	11	13	26,5	43	19	
16106016	2	13,5	16	34	51	22	
16106019	3,25	16	19	40	64	27	
16106022	4,75	19	22	46	76	31	
16106025	6,5	22	25	52	83	36	
16106028	8,5	25	28	59	95	43	
16106032	9,5	28	32	66	108	47	
16106035	12	32	35	72	115	51	
16106038	13,5	35	38	80	133	57	
16106042	17	38	42	88	146	60	
16106050	25	45	50	103	178	74	
16106057	35	50	57	111	197	83	
16106070	55	65	70	145	260	105	



### Green Pin® D-sluiting met vierkant gat G-4159

Materiaal: boog en pen van hoogwaardig staal, Grade 6

Veiligheidsfactor: 6:1

Klasse: EN 13889

Art. nr.	WLL / t	a / mm	b / mm	c / mm	d / mm	e / mm	Prijs (ex btw)
16145019	3,25	16	19	40	11	27	
16148019	4,75	19	22	46	11	31	